

STANDARD DEPARTURE  
CHART - INSTRUMENT  
(SID) - ICAODOHA/Hamad Intl.(OTHH)  
RNP RWY 34L  
LUBET 1W

## TABULAR DESCRIPTION

## RNP SID LUBET 1W

Serial Num	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation(°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA(°)/TCH(ft)	Navigation Specification
1	CF	OVASA	-	335 (338.1)	-2.6	8.0	-	+2500	-	-	RNP 1
2	TF	PARES	-	335 (338.1)	-2.6	4.5	-	@4000	-	-	RNP 1
3	TF	KOBEN	-	014 (016.5)	-2.6	10.7	-	-	-	-	RNP 1
4	TF	ALNAK	-	359 (002.1)	-2.6	11.5	-	-	-	-	RNP 1
5	TF	PATOM	-	296 (298.2)	-2.6	15.8	-	+FL160	-	-	RNP 1
6	TF	MISEL	-	318 (320.7)	-2.6	13.9	-	-	-	-	RNP 1
7	TF	LUBET	-	318 (320.6)	-2.6	7.2	-	+FL180	-	-	RNP 1

Remarks LUBET at FL180 or above and PATOM at FL160 or above by ATC only

## WAYPOINT LIST

## RNP SID LUBET 1W

Waypoint Identifier	Coordinates
OVASA	252455.76N 0513204.45E
PARES	252906.58N 0513013.12E
KOBEN	253921.98N 0513334.39E
ALNAK	255053.49N 0513401.89E
PATOM	255821.41N 0511836.36E
MISEL	260906.55N 0510850.78E
LUBET	261440.67N 0510346.54E